ELECRAFT AX-LINE ANTENNAS COMPARISON CHART

AX1

AX2

All AX-line antennas are designed for lightweight portable operation. **These whips are intended to be used <u>with an ATU</u> to compensate for terrain, body capacitance, height, inductance variance, and counterpoise length.** For details, please refer to product brochures.

	AX1	AX2	AX3
Tripod built in	-	-	**Yes (6" legs)**
1/4-20 Mount	-	-	**Yes (at base)**
BNC Orientation	Straight	Straight	**Right Angle**
Bands (with ATU)	20-17 m	20 m*	**30-10 m**
Band Switch	2 Positions	-	**4 positions**
Ground Connection	-	-	**Yes (x2) ****
Fully Disassembles	Yes	Yes	Yes
Base Length	6" (15 cm)	2.5" (6.4 cm)	6" (15 cm)
Whip (Collapsed)	6" (15 cm)	6" (15 cm)	6" (15 cm)
Whip (Extended)	45" (114 cm)	45" (114 cm)	45" (114 cm)
Power Rating	30 W	15 W	30 W
40 m Adapter	Yes	Yes	Yes
Bipod Adapter	Yes	Yes	-

*** The AX2 is also user-modifiable for 17-6 m (remove coil turns)**

**** The AX3 has both a thumb-screw ground post and a mini-banana jack (see p/n KX2GNDPLUG)**

AX3 (NEW)